




Quality Products. Service Excellence.

GR-63-CORE Critical Facility Seismic Server Cabinet *DCZ4 Series*

UL2416 rated for 3,000 lbs (1,360 kg). Static Load tested to 12,000 lbs (5,443 kg). Seismic rated up to 1,000 lbs (454 kg).



Features

- Rugged design that is engineered to perform in the most critical seismic environments.
- Numerous stud locations are included for grounding and bonding applications.
- Cable management includes
 - Four (4) 3.5" top cable access holes.
 - Various bottom panels allow for different cable management options.
 - Corner braces include mounting for cable trays and outlet strips.
 - Support for up to four optional 4" deep vertical cable managers.
- Ganging holes allow for joining multiple cabinets.
- C-channel struts provide cabinet strength, ease and flexibility to adjust mounting rails.
- Flush-mount doors come with 3-point latching and stiffeners to reduce flexing and bowing while increasing cabinet security.



Specifications

- Cabinet frame constructed in 14-gauge steel, cabinet with 12-gauge steel reinforced corner brackets.
- Cabinet doors and side panels constructed in 16-gauge steel.
- Includes two (2) pairs of EIA compliant square hole mounting rails with rack unit markings.
 - Mounting rails are constructed in 12-gauge steel and are Zinc-plated to provide superior surface areas for equipment grounding.
- Dynamic (seismic) load rated up to 1,000 lb. (454 kg) of equipment installed and 100 lb. (45 kg) of cable weight on the top. Requires a seismic bolt-down kit such as the **C4K-Z4** (sold separately). Independently tested and certified to exceed established Seismic Zone 4 NEBS™ Telcordia® GR-63-CORE testing standards.
- UL Listed 2416 load rated for up to 3,000 lbs (1,360 kg). Static Load tested to 12,000 lbs (5,443 kg).
 - Cabinet weight is not included in the above numbers.
- Grounding studs bonded to frame, side panels and doors. Front and rear studs on cabinet frame conform to PET.
- Finished in textured RAL9005 black powder paint.
- TAA-compliant for GSA Schedule purchases.
- RoHS Compliant.
- Manufactured in North America within an ISO 9001:2015 certified facility.

Included Components

- Two (2) pairs of infinitely adjustable 19" EIA compliant square hole punched rails with rack unit markings.
- Two (2) perforated front doors (63% open area vented) with locking swing handle.
- Two (2) removable solid side panels.
- One (1) removable solid top panel.

Gallery



Accessories

- Bolt Down Kit
- Rack Unit Label
- Adjustable Depth Shelf
- Four Post Mounting Sliding Shelf
- Adjustable Depth Cable Manager
- Horizontal Ring Cable Manager
- Cable Management Arm
- Vertical Cable Tray
- Rack Panels
- Vertical Cable Manager with Door
- Rack Depth Label
- Rack Equipment Installation Tool
- PDUs and Outlet Strips
- Horizontal Lacing Strip
- Horizontal Hinged Cable Manager
- Cabinet Top Panels
- Mounting Hardware
- Grounding & Bonding

Part No.	Overall Dimensions			Rack Units	Usable Mounting Dimensions		
	Height	Width	Depth		Height	Width	Depth
DCZ4A307742BK	82.81	30.00	42.00	44U	77.06	19.00	35.75

Comes complete with all components assembled.

Overall height includes leveling feet.

Optional Doors

Part No.	Part No.	Part No.
Solid Door	Window Door	63% Vented Door
DCZ4SD3077BK	DCZ4WD3077BK	DCZ4VD3077BK

Tags: **ismic**

Data subject to change without notice

© 2022. Hammond Manufacturing Ltd. All rights reserved.